

DAS-2CHD-USB

Dante® 2CH Input and Output Adapter on USB-C



Dante® Bi-directional conversion for two-channel USB audio and utilising the advanced Dante® Digital Audio. This versatile adapter is USB audio device class 1.0/2.0 compatible, supporting USB output up to 24bit/192KHz and input up to 24bit/96KHz. With Dante audio sampling rates of 24bit at 44.1, 48, 88.2, and 96KHz, it delivers exceptional audio quality

Connections

INPUT: 1x USB-C [USB-C with USB 1.0/2.0, USB audio in/out, 12-pin female]
1x POWER [USB-C power and firmware update port,12-pin female]

OUTPUT: 1x POWER [USB-C power and firmware update port,12-pin female]

Mechanical

Dimensions: 115mm [W] x 40mm [D] x 28mm [H]

Weight: 94Gm

Power Consumption : 2W(Max)



DAEWOOAV

DAS-2CHD-USB

Dante® 2CH Input and Output Adapter on USB-C

Technical:

Input/Output:	Interconverts between two-channel USB audio and Dante® 2CH digital audio
USB Audio:	1.0/2.0-compatible
Control:	Dante® Controller
Network Bandwidth:	100M
Audio Latency:	Configurable Dante® device latency (Supports 1, 2 or 5ms using Dante® Controller)
Audio Format:	DANTE IN/OUT [Digital audio output, PCM 2CH 44.1K-96KHz 16/24bit]
Audio Parameter:	USB IN Frequency Response: 20Hz to 20kHz (-/+0.5dB) Dynamic Range: >100dB@0dBu, 1kHzA-weighted Audio S/N Ratio: >100dB@0dBu, 1kHzA-weighted Audio THD+N: < 0.01% at +4dBu, 1KHz Audio Output Sync Delay: <10ms IEC 61000-4-2: ±8kV (Air-gap discharge) & ±4kV (Contact discharge)

